Care and Maintenance Instructions for **NATURAL STONE**

Shaping inspiration

ROSSKOPF +PARTNER

Stand 02/2019 — Natural Stone

All segments of your product are impregnated in our facility. Natural stone slabs have open pores; the material absorbs moisture and releases it again. By impregnating it, the penetration by moisture and dirt is largely excluded, but cannot be 100% avoided. As long as water pearls off from the surface, there is still protection from staining. If the effect lessens (this occurs normally only after many years depending on the stone), the impregnation should be reapplied.

However, you need to remove all soiling (mainly oil and grease stains) immediately to keep your product residue-free (see below). Otherwise, these can penetrate the impregnation after several hours and leave permanent stains.

YOU CAN USE NATURAL STONE IMPREGNATORS RECOMMENDED BY THE TRADE OR TRUST US WITH CONFIDENCE.

DAILY CLEANING

Removing dust:

Use our Pro-Siro[®] Maintenance Cleaner Active or an undyed glass cleaner and a soft microfiber cloth or kitchen roll.

Oil and grease contamination:

Use our Pro-Siro[®] Basic Cleaner Grease + Oil or a commercial fat remover like Bref Power against grease or Lithofin MN basic cleaner (observe the manufacturer's instructions).

Calcareous deposits and dirt:

Use our Pro-Siro cleaner, a commercial lime remover, such as Bref Power, against lime, or Lithofin MN Cement Veil Remover (follow the manufacturer's instructions).

ADDITIONAL TIPS

- Only use products specifically approved by the manufacturer to clean natural stone.
- Do not use abrasives or sponges, acidic or products containing lye.
- Do not use strong acidic products.

OUR RECOMMENDATION IN CASE OF NECESSARY REIMPREGNATION LITHOFIN CLEANING SET in plastic case (500 ml MN basic cleaner, 250 ml Stain Stop, 500 ml MN Easy Clean)

ROSSKOPF + PARTNER AG

Telephone +49 (0) 36021 9899-0 · E-Mail info@rosskopf-partner.com · Web rosskopf-partner.com